

PRODUCT INFORMATION

GerberMask ULTRA

GerberMask ULTRA is a 4 mil white vinyl film, coated with a low-tack removable adhesive now on a ***new moisture resistant liner***. Designed to be used as stencil masking film for application to a variety of smooth, flat substrates. The low-tack adhesive allows easy removal from substrates, with no adhesive transfer. Suitable for use on glass, Plexiglas, polycarbonate, flexible vinyl, stainless steel.

NOTE: GerberMask ULTRA has a low-tack adhesive for easyremoval from high energy surfaces. Rough, uneven, or curved surfaces may require a more aggressive adhesive. GerberMask ULTRA II stencil mask with high-tack adhesive is available if greater substrate adhesion is required.

GerberMask Yellow ULTRA

GerberMask Yellow ULTRA is a 4 mil yellow vinyl film, coated with a ***low-tack removable adhesive*** on a paper liner developed as a high contrast stencil for painted graphics for application to a variety of smooth, flat surfaces. The yellow face film makes weeding and application easier especially when the stencil is applied to a white surface.

GerberMask ULTRA II

GerberMask ULTRA II is a durable, conformable 4 mil white vinyl film, coated with ***aggressive*** acrylic removable adhesive now on a ***new moisture-resistant liner.*** Designed to hold during light sandblasting, acid etching, or paint applications. Removable, with no adhesive transfer. Suitable for use on glass, Plexiglas, stainless steel, unfinishedand finished wood surfaces. **DO NOT APPLY GerberMask ULTRA II TO FLEXIBLE VINYL FILM.**

NOTE: GerberMask ULTRA II has a high-tack adhesive that will adhere strongly to smooth, high-energy substrates,such as Plexiglas or polycarbonate. Requires some effort to remove. GerberMask ULTRA, with low-tack adhesive, may be more suitable for this type of application. GerberMask ULTRA can be used on flexible vinyl substrates.

GRAPHIC Marking Systems™

www.shopGMS.com
847.582.9276 ▪ 800.232.8018
orders@graphicms.com

GerberMask™

General Description: **GerberMask Ultra** has been developed as a replacement for GerberMask I. GerberMask Ultra is a 4-mil, white film with a low-tack adhesive system for use as a stencil mask on smooth, flat surfaces. **GerberMask Yellow Ultra** is a 4-mil, yellow film with a low-tack adhesive system. **GerberMask Ultra II** is a 4-mil, white film with an aggressive, removable, acrylic adhesive and layflat liner construction.

FEATURE	ULTRA	YELLOW ULTRA	ULTRA II
THICKNESS	4 mil	4 mil	4 mil
FILM COLOR	White	Yellow	White
ADHESIVE	Low-tack removable	Low-tack removable	Aggressive acrylic removable
LINER	Moisture-stable	Paper	Moisture-stable
FLEXIBLE VINYL	✓**Yes**	✓**Yes**	×**No**
SANDBLASTING	Light	Light	Ligh-Moderate
ACID ETCHING	✓	✓	✓-Preferred
MIN. APP TEMP	40˚F (4˚C) - All variants		
SHELF LIFE	1 Year from purchase		

SHELF LIFE AND STORAGE

GerberMask can be stored for one year after purchase. Film should be stored vertically using original packaging material and kept in a clean area free from excessive moisture and direct sunlight. Maintain temperature at less than 75°F (23°C) and a maximum of 70% RH.

CUTTING

GerberMask can be cut on any Gerber sprocketed or friction plotter. Plotters should be set to 50% speed. A 45° SuperSharp blade is recommended. For optimal results, a test cut should be performed with as little weight as possible and gradually increased until the vinyl layer is completely cut and the liner is lightly scored. Using too much weight or attempting to cut the film too fast will cause it to bind in your plotter.

RECOMMENDED APPLICATION TECHNIQUES:

Cut the GerberMask then weed as a stencil. Transfer the stencil onto the sign surface using low tack application tape. Apply the paint within the stencil by hand, airbrush or spray paint. Not for use with lacquer based paints. Remove the mask when the paint is just dry to the touch. Leaving the mask on longerthan necessary could make it difficult to remove.

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application.