

PRODUCT CHARACTERISTIC SHEET and COC

PLEASE READ BEFORE USING!

Material: High-Bond Clear Transfer Adhesive

Part Nos: TASHB1350C

General Description: Clear pressure sensitive aggressive permanent transfer adhesive self wound with a white paper liner. Use with compatible sub-surface printable "Armalex" polycarbonate for application to low energy plastic, powder paint and most other surfaces.

Thickness:	2 mil. of transfer adhesive.	Adhesive Properties: High performance, aggressive permanent acrylic pressure sensitive adhesive formulated for bonding to low surface energy materials such as plastic and powder painted surfaces.
Outdoor Life:	2+ years	
Shelf Life:	2 years stored at 70° F & 50%RH	
Service Temperature Range:	(-40° F to 302° F)	
Minimum Application Temp.:	50° F	

Tests performed | results:

Ultimate Peel from	Average OZ/IN	Test Method	
Acrylic	105	ASTM D 903 (Modified for 72 hour dwell time)	
Glass	107		
Polypropylene	10		
Stainless Steel	94		
Expected Shear Room Temp (hours)	30	ASTM D 3654 Method A	a. 1 hrl dwell b. 1 sq. in. surface c. 4 lb. load
Tack (gm/sq cm)	1650	ASTM D 2979	

CERTIFICATE OF CONFORMANCE (COC)

Sold to:		Lot No.:	
Buyer:		PO#	
		Supplier's Authorized Rep.:	
Supplier:	Graphic Marking Systems	MFR Part No:	Top of the page
		Title:	
MFR Date:		Ship Date:	
		Date:	

Recommended Application Techniques:

Laminate with cold or low heat assist laminator. Not recommended for very soft vinyl such as static cling. High-Bond is intended to be permanent, but may be removed without residue from certain plastics. Depending on the surface, High-Bond may not be repositionable.

GSP Software Settings:

Little if any cutting pressure needs to be added, because the film is so thin.

USE A 45° blade or 60° BLADE on any combination of material 8 mil or thicker.

Disclaimer:

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Although this material can be printed on with some solvent based printers, the surface characteristics of the material can change from roll to roll, and failure of optimal printing results are not a basis for returning the product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application. GMS0612 Graphic Marking Systems

Material Safety Data Sheet (MSDS)

Material Name: High-Bond Clear Transfer Adhesive				Company:				
Part Nos: TASHB1350C				Graphic Marking Systems				
Date Prepared: 8/25/2015				Address: 28457 N. Ballard Rd., Suite A1 Lake Forest, IL 60045				
General Description: Clear pressure sensitive aggressive permanent transfer adhesive self wound with a white paper liner.				Phone: 847-582-9276 Fax: 847-582-9282				
Composition and information on ingredients: Individual components of this product do not contribute to any known hazards. OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200): NONE						UL Recognized:		NO
						ROHS Compliant:		YES
						REACH Compliant:		YES
Hazards Identification:								
POTENTIAL HEALTH EFFECTS: None								
ACUTE: No significant toxic hazard. When burned may produce toxic fumes.								
CHRONIC: No significant toxic hazard.								
None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.								
First Aid Measures:					Fire Fighting Measures:			
Emergency and First Aid Procedures:					Flash Point: N/A			
ROUTES OF ENTRY:					Method Used: N/A			
Inhalation: N/A Skin: N/A					Auto-ignition Temperature N/A			
Eyes: N/A Ingestion: N/A					Flamable limits in Air % by Volume: LEL: N/A, UEL: N/A			
Accidental Release Measures: N/A					Extinguishing Media: Multi-rated ABC extinguisher or water			
Handling and Storage:					Unusual Fire and Explosion Hazards: None			
No special handling required other than storing away from excessive heat sources.					Special Fire Fighting Procedures: In case of fire, use self-contained breathing apparatus and full protective equipment - all fires liberate toxic gases.			
Exposure Controls and Personal Protection:					Physical and Chemical properties:			
Respiratory Protection: None required					Vapor Pressure (mm Hg) N/A		Boiling Point: N/A	
Skin Protection: No precautions required					Vapor Density (air = 1): N/A		Melting Point: N/A	
Eye Protection: None required					Appearance and odor: N/A		Reactivity of water: N/A	
Exposure Guidelines: None established					Specific Gravity (H 0=1) N/A		Solubility in water: N/A	
Engineering Controls: None required					Stability and Reactivity:			
Toxicological Information:					Stability: N/A			
Carcinogen Status: NTP: NONE IARC: NONE OSHA: NONE					Conditions to avoid: Fire or Excessive Heat			
Ecological Information: No Data Availble					Incompatibility: None			
Transport Information:					Hazardous Decomposition Products: None			
TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION: Not a hazardous material for DOT shipping.					Hazardous Polymerization: Will not occur.			
Disposal Considerations: Waste Disposal: Dispose of in accordance with Local, State and Federal regulations.					Regulatory Information:			
Other Information:					OSHA STANDARD CFR 29, PART 1910.1200: This product is considered to be an "article" under this standard.			
The information contained herein is based on the data available to Graphic Marking Systems, and is believed to be correct. However, Graphic Marking Systems makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Graphic Marking Systems assumes no responsibility for injury from the use of the product described herein.					SARA 313 INFORMATION: This product contains no substances at or above the reporting threshold subject to the reporting requirement of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 371, based on available data.			
					CALIFORNIA PROPOSITION 65: CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. Warning this product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.			