

PRODUCT INFORMATION

Need a material that will prevent slipping for both wet and dry surfaces? **Stubbl™** is a heavily textured, crystal clear, flexible laminate that adds non-slip characteristics to the surface or media it's applied to. This laminate is an 18 mil thick film designed for applications where solid traction or grip is needed. It works well with or without graphics and can also be used for counter tops and graphics when a different look is desired.

Stubbl works whether wet or dry, and therefore is recommended for watercraft, tubs, swim platforms, surf boards, and stand-up paddle boards. It is also great for motor bikes, quads, and other recreational vehicles. Stubbl exceeds OSHA and ADA standards for non-slip protection on hazardous surfaces, and it is certified as "high traction" by the NFSI.

Get a sample of Stubbl! Contact at orders@graphicms.com.

IN STOCK! ORDER NOW AT www.shopGMS.com!

NOTABLE QUALITIES

SWIM PLATFORMS

Provide traction, reducing the risk of slipping when the platform is wet.

CARPET DECALS

Decals specifically designed to be applied to carpeted surfaces.

EXTRA GRIP

The surface of the decal may have a textured or anti-slip finish, providing better footing for people walking on it.

EASY TO CUT

The material can be adjusted to fit specific dimensions, shapes, or designs.

GRAPHIC Marking Systems™

www.shopGMS.com
847.582.9276 ▪ 800.232.8018
orders@graphicms.com

Stubbl™

NON-SLIP LAMINATE

General Description: This heavily textured clear flexible laminate provides non-slip characteristics to the surface or media it is applied to. Stubbl works when it is dry or wet and therefore is recommended for watercraft and tubs as well as bikes and other recreational vehicles. This film exceeds OSHA & ADA standards for non-slip protection on hazardous surfaces.

PRODUCT SPECIFICATIONS



TECHNICAL PROPERTIES:

Thickness: 15-16 mil embossed vinyl, plus 2 mils of adhesive

Outdoor Life: 2 years

Shelf Life: 1 year stored at 70° F & 50% RH

Adhesive Properties: Permanent acrylic

Service Temperature Range: -20° F to 175° F (-32°C to 40°C)

Minimum Application Temperature: 50° F (10°C)

RECOMMENDED APPLICATION TECHNIQUES:

Apply to clean, dry, lubricant-free surfaces. If you intend to apply Stubbl to solvent ink jet prints, we strongly suggest that you let the prints dry for at least an hour before laminating. The end user is responsible for determining the exact dry times for the ink and media combination they are using.

Cut testing has been done with the Gerber enVision 375 plotter only. Stubbl is an embossed vinyl and can be cut with plotters that can accept thick laminate materials. We suggest using double cuts whenever possible and adjust the knife out to the thickness you need to cut. The end user is responsible for determining the exact cutting force media combination they are using. We suggest cutting with a 60° or 45° blade.

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application.

GMS012026 GRAPHIC MARKING SYSTEMS