

PRODUCT CHARACTERISTIC SHEET and COC

PLEASE READ BEFORE USING!

Material: **WET LOOK LAMINATE 1 mil, UL recognized**



General Description: Clear, high gloss polyester with a crystal clear, pressure sensitive, permanent adhesive on a clear film liner. This film is used for protective overlaminating and a high gloss "wet look."



UL Recognition has been obtained for Wet Look 1 mil laminate. When laminated to White High-Bond polyester that has been printed with Gerber GCS spot color foils, or the HP Latex ink jet with 873 Series Latex inks, the full label construction is UL recognized for both the U.S and Canada. Latex ink does not pass the rub test without the Wet-Look laminate. The same UL Recognition has been obtained when laminating Wet Look to Ptibull Industrial polyester (US Only). More information may be found by downloading the UL recognition file MH28890 from: <https://www.shopgms.com/laminates/industrial-lam/wet-look.html>

Thickness:	1 mil. polyester with 1 mil (+/- .1) of adhesive.	Adhesive Properties: High performance, permanent solvent-based acrylic pressure sensitive adhesive formulated for overlaminating thermal and latex printed markings. It is also likely to be compatible with other formats of printing.
Outdoor Life:	2 years	
Shelf Life:	2 years stored at 70° F & 50%RH	
Service Temperature Range:	(-40° F to 302° F)	
Minimum Application Temp.:	50° F	

Tests performed | results:

Ultimate Peel from	Average OZ/IN	Test Method	
Acrylic	77	ASTM D 903 (Modified for 72 hour dwell time)	
Glass	52		
Polypropylene	18		
Stainless Steel	45		
Expected Shear Room Temp (hours)	75	ASTM D 3654 Method A	a. 1 hrl dwell b. 1 sq. in. surface c. 4 lb. load
Tack (gm/sq cm)	310	ASTM D 2979	

CERTIFICATE OF CONFORMANCE (COC)

Sold to:		Lot No.:	
Buyer:		PO#	
Supplier: Graphic Marking Systems	MFR Part No:	Top of the page	Supplier's Authorized Rep.: Demas Garcia Converting Manager
MFR Date:	Ship Date:		Title:
			Date:

Recommended Application Techniques:

Laminate with a cold pressure sensitive laminator, not by hand. Separate from backing with a knife or razor blade and fold a corner under for easier handling. Be aware if laminating on top of vinyl. In many cases, the vinyl will shrink (polyester will not) and force the laminate to bubble up and possibly delaminate.

GSP Software Settings:

Little if any cutting pressure needs to be added, because the film is so thin.

USE A 45° blade or 60° BLADE on any combination of material 8 mil or thicker.

Disclaimer:

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Although this material can be printed on with some solvent based printers, the surface characteristics of the material can change from roll to roll, and failure of optimal printing results are not a basis for returning the product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application. GMS0824 Graphic Marking Systems

Material Safety Data Sheet (MSDS)

Material Name: 1 Mil WET LOOK LAMINATE		Company:							
Part Nos: PY113120C,PY11120C,PY111200C		Graphic Marking Systems							
Date Prepared: 8/16/2024		Address: 28457 N. Ballard Rd., Suite A1							
General Description: Clear, high gloss polyester with a crystal clear, pressure sensitive, permanent adhesive on a clear film liner. Wet Look is UL recognized for both the U.S and Canada.		Lake Forest, IL 60045							
		Phone: 847-582-9276							
		Fax: 847-582-9282							
Composition and information on ingredients:		UL Recognized: YES	3TG Compliant: YES						
Individual components of this product do not contribute to any known hazards.		UL File MH28890 	ROHS Compliant: YES						
OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200): NONE			REACH Compliant: YES						
Hazards Identification:		Indirect Food Contact Compliant: 21 CFR 177.1630 & 21 CFR 175.105							
<table style="width: 100%; border: none;"> <tr> <td style="width: 20%;">POTENTIAL HEALTH EFFECTS:</td> <td>None</td> </tr> <tr> <td>ACUTE:</td> <td>No significant toxic hazard. When burned may produce toxic fumes.</td> </tr> <tr> <td>CHRONIC:</td> <td>No significant toxic hazard.</td> </tr> </table>				POTENTIAL HEALTH EFFECTS:	None	ACUTE:	No significant toxic hazard. When burned may produce toxic fumes.	CHRONIC:	No significant toxic hazard.
POTENTIAL HEALTH EFFECTS:	None								
ACUTE:	No significant toxic hazard. When burned may produce toxic fumes.								
CHRONIC:	No significant toxic hazard.								
None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.									
First Aid Measures:		Fire Fighting Measures:							
Emergency and First Aid Procedures:		Flash Point: N/A							
ROUTES OF ENTRY:		Method Used: N/A							
Inhalation: N/A	Skin: N/A	Auto-ignition Temperature: N/A							
Eyes: N/A	Ingestion: N/A	Flamable limits in Air % by Volume: LEL: N/A, UEL: N/A							
Accidental Release Measures: N/A		Extinguishing Media: Multi-rated ABC extinguisher or water							
Handling and Storage:		Unusual Fire and Explosion Hazards: None							
No special handling required other than storing away from excessive heat sources.		Special Fire Fighting Procedures: In case of fire, use self-contained breathing apparatus and full protective equipment - all fires liberate toxic gases.							
Exposure Controls and Personal Protection:		Physical and Chemical properties:							
Respiratory Protection: None required	Vapor Pressure (mm Hg) N/A								
Skin Protection: No precautions required	Boiling Point: N/A								
Eye Protection: None required	Vapor Density (air = 1): N/A								
Exposure Guidelines: None established	Melting Point: N/A								
Engineering Controls: None required	Appearance and odor: N/A								
		Reactivity of water: N/A							
		Specific Gravity (H 0=1) N/A							
		Solubility in water: N/A							
Toxicological Information:		Stability and Reactivity:							
Carcinogen Status: NTP: NONE IARC: NONE OSHA: NONE		Stability: N/A							
Ecological Information: No Data Available		Conditions to avoid: Fire or Excessive Heat							
Transport Information:		Incompatibility: None							
TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION: Not a hazardous material for DOT shipping.		Hazardous Decomposition Products: None							
Disposal Considerations: Waste Disposal:		Hazardous Polymerization: Will not occur.							
Dispose of in accordance with Local, State and Federal regulations.		Regulatory Information:							
Other Information:		OSHA STANDARD CFR 29, PART 1910.1200: This product is considered to be an "article" under this standard.							
The information contained herein is based on the data available to Graphic Marking Systems, and is believed to be correct. However, Graphic Marking Systems makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Graphic Marking Systems assumes no responsibility for injury from the use of the product described herein.		SARA 313 INFORMATION: This product contains no substances at or above the reporting threshold subject to the reporting requirement of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 371, based on available data.							
		CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. Warning this product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. This product contains up to 0.23% Toluene in the adhesive.							

