


# POLI-TAPE™



*Poli-Tapes are designed for the quick and easy transfer of computer cut vinyl letters, logos, and designs, from the original carrier sheet to the finished surface. Such surfaces include windows, appliances, automobiles, powersport vehicles, and many other applications. These high quality semi-transparent tapes have a natural latex adhesive and are available in various lengths.*

## PRODUCT INFORMATION

### POLI-TAPE™ 130 MILKY WHITE

Poli-Tape 130 is a milky white all-purpose application tape that lays flat and tears with very little adhesive webbing. Featuring excellent stability of shape, Poli-Tape 130 won't curl under moist conditions. Tape translucence simplifies alignment of graphics.

### POLI-TAPE™ 160 CLEAR

Poli-Tape 160 is an embossed clear polypropylene film for applications requiring precise registration, such as retail kiosks, door/window lettering, and vehicle detailing. Poli-Tape 160 has superb lay-flat characteristics, making it a great choice for use over decals being stacked and stored, or rolled and shipped.

Order Poli-Tape at [www.shopGMS.com](http://www.shopGMS.com) in bulk cases or single rolls today! We stock a wide variety of lengths to choose from.

Scan to order! ▶



## NOTABLE QUALITIES

- Virtually static free, resulting in trouble-free application
- Exceptional clarity for easy, accurate registration
- Protects your graphics prior to and during application
- Easy removal, leaving no adhesive residue behind



# POLI-TAPE™

## PRODUCT SPECIFICATIONS

### RECOMMENDED APPLICATION TECHNIQUES:

**Poly-Tape 130** application tape based on a special impregnated paper with low tensile elongation and high wet strength.

Suitable for transferring self adhesive letters produced from cast and calendered PVC colored films according to CAD/CAM techniques.

Properties to be emphasized are the following:

- The natural rubber adhesive guarantees an excellent adhesion on PVC films because of the relatively high coating weight.
- The impregnated carrier paper shows an excellent stability of shape, with no curl even under moist conditions.
- Based on the tape translucence, the alignment – even of small letterings and logos – is simplified.
- The application tape can be rewound easily from the roll.

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

*All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application.*

DEI/GMS0223 GRAPHIC MARKING SYSTEMS

### TECHNICAL PROPERTIES:

| Poly-Tape         | 130                        | 160                                  |
|-------------------|----------------------------|--------------------------------------|
| Width (inches)    | 1, 2, 3, 4, 12, 14, 24, 30 | 1, 2, 3, 4, 6, 8, 10, 12, 14, 24, 48 |
| Length (in yards) | 100                        | 100                                  |
| Color             | White                      | Clear                                |

**Poly-Tape 160** transparent application tape based on a single sided embossed Polypropylene film, with excellent flatness. It is dimensionally stable, easy to unroll, position and will not stretch or curl.

Suitable for transferring self adhesive signs, logos and lettering produced from cast or calendered CAD/CAM plotter films with matte or brilliant surface.

Properties to be emphasized are the following:

- As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.
- The plasticizer resistant adhesive guarantees a strong initial tack to all types of vinyl films. The application tape is easily removed without leaving any residue, even after being left for a period of time.
- Suitable for wet application.
- The film can be torn transversally, which facilitates handling.
- The embossed surface allows the film to be easily unrolled without any accumulation of electrostatic charging.